



Modular tower light to serve most of your industrial needs

Harmony XVB Ø 70mm modular tower light

Harmony XVB provides visual and audible signaling units to indicate the status of a machine throughout 360° and at a distance.



Modularity

- Totally flexible construction of up to 5 lens units (six colours of illuminated lens unit): simple interchangeability of units.
- 3 types of light source: 10 Watt incandescent bulb, built-in high-efficiency LEDs, 5 and 10-joule discharge tube.

High performance

- A high degree of protection: IP66.
- 100,000 hours of maintenance-free lighting thanks to “LED Protected” technology.

Flexibility

- Connector with removable base, axial, or side cable entry, immediate assembly, and fixing using a locking ring.
- Various mounting option as accessories are available to cater for most industrial situation



se.com

Life Is On

Schneider
Electric

How to select

1. Select the lens unit according to your voltage & light pattern requirement
 1. Can select up to 5 device
 2. Audible is part of the selection
2. Select your body/base
3. Select the type of accessories.



Part 1: Modules

Illuminated units for tower light or beacon



Flash beacon:
5J or 10J



Flash unit:
5J or 10J



Steady beacon:
Bulb or LED



Steady unit:
Bulb or LED



Blinking beacon:
Bulb or LED



Blinking unit:
Bulb or LED

Audible Unit



Buzzer adjustable
from 70 to 90dB

Part 2: Base

Base Unit



Universal Voltage depending
on type of Lens used

Part 3: Accessories

Several options parts



se.com



Life Is On

Schneider
Electric